

FIAT GRANDE PANDA		RED (ELECTRIC)	LA PRIMA (ELECTRIC)	POP (HYBRID)	ICON (HYBRID)	LA PRIMA (HYBRID)
DIMENSIONS	Length [mm]	3.999	3.999	3.999	3.999	3.999
	Height [mm]	1.570	1.573	1.586	1.586	1.585
	Height (w/ Antenna) [mm]	1.581 on antenna fixed base	1.615 on roof rails	antenna not present	1.598 on antenna fixed base	1.629 on roof rails
		(1.801 on antenna removable part)	(1.803 on antenna removable part)		(1.818 on antenna removable part)	(1.818 on antenna removable part)
	Width [mm]	1.763	1.763	1.763	1.763	1.763
	Width (w/ Mirrors) [mm]	2.017	2.017	2.017	2.017	2.017
	Wheelbase [mm]	2.540	2.540	2.540	2.540	2.540
	Wheelsize	TOD 652	TOD 658	TOD 652	TOD 652	TOD 658
	Front Overhang [mm]	788	788	788	788	788
	Rear Overhang [mm]	671	671	671	671	671
	Ground Clearance [mm, standard A]	160	161	183	183	182
	Boot volume [L]	361 l	361 l	412 l	412 l	412 l
		(350 liquid above carpet+11 bricks below carpet without tyre kit cargo box)	(350 liquid above carpet+11bricks below carpet without tyre kit cargo box)	(350 liquid above carpet + 62 bricks below carpet without tyre kit cargo box)	(350 liquid above carpet + 62 bricks below carpet without tyre kit cargo box)	(350 liquid above carpet + 62 bricks below carpet without tyre kit cargo box)
	Boot volume w/ folded seats [L]	1.315 l	1.315 l	1.366 l	1.366 l	1.366 l
		(1.304 liquid + 11 bricks below trunk carpet without tyre kit cargo box)	(1.304 liquid + 11 bricks below trunk carpet without tyre kit cargo box)	(1.304 liquid + 62 bricks below carpet without tyre kit cargo box)	(1.304 liquid + 62 bricks below carpet without tyre kit cargo box)	(1.304 liquid + 62 bricks below carpet without tyre kit cargo box)
BRAKES	Tire Information	205/60R16	205/55R17	205/60R16	205/60R16	205/55R17
	Number of Seats	5	5	5	5	5
	Front	Disc	Disc	Disc	Disc	Disc
SUSPENSIONS	Rear	Disc	Disc	Disc	Disc	Disc
	Front	Mac Pherson	Mac Pherson	Mac Pherson	Mac Pherson	Mac Pherson
STEERING	Rear	Twist Beam	Twist Beam	Twist Beam	Twist Beam	Twist Beam
	Power (torque max / Absorption)	75Nm (100A max)	75 Nm (100A max)	75Nm (100A max)	75Nm (100A max)	75 Nm (100A max)
	Ratio	51,5 mm/ rev	51,5 mm/rev	51,5 mm/ rev	51,5 mm/ rev	51,5 mm/rev
	Turn lock to lock (revs / deg)	3,1 / 1118	3,1 / 1118	3,1 / 1118	3,1 / 1118	3,1 / 1118
WEIGHTS	Kerb to kerb turning cycle [m]	10,9	10,9	10,9	10,9	10,9
	Kerb Weight [kg]	1.532	1.554	1.315	1.327	1.347
	Weight Standard A [kg]	1.457	1.479	1.240	1.252	1.272
	Max Payload (including driver) [kg]	453	431	460	448	428
	Battery [kg]	350	350	12	12	12
	Towing [kg]	550	550	600	600	600
PERFORMANCES	Hybrid System Combined Power [kW] / [CV]	-	-	81 / 110**	81 / 110**	81 / 110**
	Electric motor Power [kW] / [CV]	83 / 113	83 / 113	21 / 28	21 / 28	21 / 28
	Thermal engine Power [kW] / [CV]	-	-	74 / 100	74 / 100	74 / 100
	Max Torque [Nm]	122	122	205	205	205
	Traction	FWD	FWD	FWD	FWD	FWD
	WLTP Consumption - Combined [kWh/100km]	16,8	16,8	-	-	-
	WLTP Range - Combined [km]	320	320	-	-	-
	CO2 Emissions - Combined [g/km]	-	-	116	115*	117
	Consumption - Combined [L/100 km]	-	-	5,1	5,0*	5,1
	Top Speed [km/h]	132	132	160	160	160
	Acceleration 0-100 km/h [s]	11	11,5	11,2	11,2	11,2
	Acceleration 0-50 km/h [s]	4,2	4,2	-	-	-
	Technology	LFP	LFP	NMC	NMC	NMC
	Total Voltage [Volts]	400V	400V	48V	48V	48V
BATTERY AND CHARGING	Battery Capacity [kWh]	44kWh	44kWh	0,876kWh	0,876kWh	0,876kWh
	Battery Capacity (Net) [kWh]	43,8	43,8	-	-	-
	Charge Port	CCS Type2	CCS Type2	-	-	-
		+ spiral cable	+ spiral cable	-	-	-
	AC On-Board-Charger [kW]	7kW (11kW + NO spiral cable	7kW (11kW + NO spiral cable	-	-	-
	DC Fast Charger [kW]	100kW	100kW	-	-	-
	Charging Time [h:min] (AC 7kW - 20-80%)	04:20	04:20	-	-	-
	Charging Time [h:min](AC 11kW - 20-80%)	02:50	02:50	-	-	-
	Charging Time (DC 100kW - 20-80%)	00:27	00:27	-	-	-
ENGINE	Engine name	M2 EDM	M2 EDM	T-Gen3	T-Gen3	T-Gen3
	Kind of engine			3 cylinders - turbo	3 cylinders - turbo	3 cylinders - turbo
	Displacement [cm ³]	-	-	1.2l	1.2l	1.2l
	Euro Emission Class	-	-	€6.4	€6.4	€6.4
	Gearbox	-	-	eDCT	eDCT	eDCT
	Fuel Tank [L]	-	-	44l	44l	44l